

USSN 10/635,270

PATENT

Uber et al.

- 2 -

IN THE CLAIMS:

Please cancel Claims 2, 7, 8 and 19 without prejudice and amend Claims 1, 11, and 17-20 as set forth below. The following is a listing of the claims currently pending in the application.

1. (currently amended) A photoacoustic detector for measuring an analyte gas in an environment, the photoacoustic detector comprising:

a source of optical energy;

a sensing volume, the sensing volume being in fluid connection with the environment through an acoustic pressure attenuating element such that the analyte gas can diffuse into the sensing volume through the acoustic pressure attenuating element; and

an acoustic pressure sensor volume including an acoustic pressure sensor, the acoustic pressure sensor volume being in fluid connection with the sensing volume through a capillary tube such that the initial response time of the photoacoustic detector is independent of the size of the acoustic pressure sensor volume relative to the size of the sensing volume.

2. (canceled)

3. (original) The photoacoustic detector of claim 1 wherein the fluid connection between the acoustic pressure sensor volume and the sensing volume is placed in close proximity to the acoustic pressure attenuating element.

USSN 10/635,270

PATENT

Uber et al.

- 3 -

4. (original) The photoacoustic detector of claim 1 wherein the fluid connection between the acoustic pressure sensor volume and the sensing volume is placed near a corner of the sensing volume in close proximity to the acoustic pressure attenuating element.

5. (original) The photoacoustic detector of claim 1 wherein the fluid connection between the acoustic pressure sensor volume and the sensing volume is placed near an edge of the sensing volume in close proximity to the acoustic pressure attenuating element.

6. (original) The photoacoustic detector of claim 1 wherein the diffusion rate of the analyte gas from the sensing volume into the acoustic pressure sensor volume through the fluid connection is less than the diffusion rate of the analyte gas from the environment into the sensing volume through the acoustic pressure attenuating element.

7-8. (canceled)

9. (original) The photoacoustic detector of claim 1 wherein the sensing volume and the acoustic pressure sensor volume are similar in size.

10. (original) The photoacoustic detector of claim 1 wherein the sensing volume is less than the acoustic pressure sensor volume.

11. (currently amended) A photoacoustic detector for measuring an analyte gas in an environment, the photoacoustic detector comprising:

a source of optical energy;

USSN 10/635,270

PATENT

Uber et al.

- 4 -

a sensing volume, the sensing volume being in fluid connection with the environment through an acoustic pressure attenuating element such that the analyte gas can diffuse into the sensing volume through the acoustic pressure attenuating element;

an acoustic pressure sensor volume similar in size to the sensing volume and including an acoustic pressure sensor; and

a connector between the acoustic pressure sensor volume and the sensing volume such that the diffusion of the analyte gas from the sensing volume to the acoustic pressure sensor volume is controlled without adversely affecting the transmission of the photoacoustic pressure signal between the sensing volume and the acoustic pressure sensor volume.

12. (original) The photoacoustic detector of claim 11 wherein the connector between the acoustic pressure sensor volume and the sensing volume functions as a capillary tube.

13. (original) The photoacoustic detector of claim 11 wherein the connector between the acoustic pressure sensor volume and the sensing volume is placed in close proximity to the acoustic pressure attenuating element.

14. (original) The photoacoustic detector of claim 11 wherein the connector between the acoustic pressure sensor volume and the sensing volume is placed near a corner of the sensing volume in close proximity to the acoustic pressure attenuating element.

15. (original) The photoacoustic detector of claim 11 wherein the connector between the acoustic pressure sensor volume and the sensing volume is placed near an edge of the sensing volume in close proximity to the acoustic pressure attenuating element.

USSN 10/635,270

PATENT

Uber et al.

- 5 -

16. (original) The photoacoustic detector of claim 11 wherein the diffusion rate of the analyte gas from the sensing volume into the acoustic pressure sensor volume through the connector is less than the diffusion rate of the analyte gas from the environment into the sensing volume through the acoustic pressure attenuating element.

17. (currently amended) The photoacoustic detector of claim 11 wherein the connector between the acoustic pressure sensor volume comprises a gas permeable flexible membrane.

18. (currently amended) The photoacoustic detector of claim 11 wherein the connector between the acoustic pressure sensor volume and the sensing volume comprises a rigid membrane mounted in a flexible support and having a hole therein to permit steady-state pressure equalization.

19. (canceled)

20. (currently amended) The photoacoustic detector of claim [11] 1 wherein the sensing volume is [less] larger than the acoustic pressure sensor volume.